

"Express Mail" mailing label number ER 213371840 US

PATENT APPLICATION
DOCKET NO. 10017463-4

IMAGING APPARATUS AND METHODS

INVENTOR:

Eric Eskey

IMAGING APPARATUS AND METHODS

FIELD OF THE INVENTION

The invention claimed and disclosed herein pertains to imaging apparatus and methods, and more specifically, to apparatus and methods for supporting multiple types of imaging media on an imaging device having only one pick roller.

BACKGROUND OF THE INVENTION

Various forms of imaging devices are known in the art. Imaging devices are those devices that are configured to produce an image on an imaging media. Imaging devices are known by various names in accordance with specific applications thereof, which include those of printers, facsimile machines, photocopiers, and the like. Imaging devices can also include integral units (commonly known as "all-in-one" devices) which combine the functionality of two or more of the aforementioned exemplary imaging devices. Imaging media that is used in conjunction with the production of images is generally in the form of paper sheets, but can be in other forms such as plastic transparency sheets, envelopes, cardstock, and labels. In order to form an image, an imaging device deposits a substance such as ink, dye, toner, or the like onto the imaging media to form the image.

Prior art imaging devices are generally configured to accept more than one size and/or configuration of the imaging media in order to facilitate versatility of use. For example, a typical prior art imaging device can be configured to accept different sizes of paper sheets, and/or can be configured to accept envelopes in addition to letter-sized paper sheets. In general, the more basic economy imaging devices are configured to allow only one form of imaging media to be placed into the imaging device at a time. For example, a basic printer has only one imaging media tray that is adjustable so as to accept different sizes and types of imaging media.

In such a printer having only one media tray, the imaging media must be physically removed and replaced whenever the size or type of media is changed. For example, to print a document, a plurality of letter-sized paper sheets is placed into the media tray of the printer. The document is printed on the letter-sized sheets of paper. Then, to print an address on an envelope, the remaining letter-sized sheets of media are removed from the media tray, and an envelope is placed into the tray. The address is printed on the envelope. In order to print another document, the letter-sized imaging media would again be placed into the media tray of the printer.

1 Larger, more advanced imaging devices generally include a plurality of media
2 trays for holding various types and/or sizes of imaging media or the like. For example, a
3 typical prior art advanced printer generally has several media trays. In such a printer,
4 one of the media trays is generally configured to hold standard letter-sized paper sheets,
5 while another of the media trays is configured to hold legal-sized paper sheets. Yet
6 another of the media trays can be configured to hold standard-sized envelopes. This
7 type of arrangement can be advantageous because different types of imaging media and
8 envelopes can be utilized in a single imaging device without the need for removal and
9 replacement of the imaging media and/or envelopes each time a different type and/or
10 size of media is called for.

11 However, with regard to these more advanced prior art imaging devices which
12 employ a plurality of media trays, the media handling means which are configured to
13 accommodate the multiple media trays can be overly complex and can occupy an extra
14 amount of space. For example, such prior art imaging devices having a plurality of
15 media trays employ a separate pick roller, and related drive and control system, for each
16 media tray. In addition, multiple media paths and related media conveyance means are
17 required to move each of the different types of media from the respective media tray to
18 the imaging section where the image is transferred to the media.

19 What are needed then are imaging apparatus and methods which achieve the
20 benefits to be derived from similar prior art methods and/or devices, but which avoid the
21 shortcomings and detriments individually associated therewith.

22 23 SUMMARY OF THE INVENTION

24 The instant invention provides for supporting two or more types of imaging media
25 on an imaging apparatus having only a single pick roller. That is, in accordance with
26 various embodiments of the present invention, an imaging apparatus can employ a
27 single pick roller to selectively pick one of two or more types of imaging media which are
28 supported in respective media trays. This is accomplished by employing an actuating
29 mechanism that is configured to selectively position any of the media trays relative to the
30 pick roller so that the respective imaging media is presented to the pick roller for picking.
31 These and other aspects and embodiments of the present invention will now be
32 described in detail with reference to the accompanying drawings, wherein:

DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic diagram which depicts an imaging apparatus in accordance with one embodiment of the present invention.

Fig. 2 is a schematic diagram which depicts the imaging apparatus shown in Fig. 1, with the first and second media trays shown in different positions relative to the pick roller.

Fig. 3 is a side elevation sectional view of an imaging apparatus in accordance with another embodiment of the present invention, with some components not shown.

Fig. 4 is a side elevation sectional view of the imaging apparatus shown in Fig. 3, with the first and second media trays shown in different positions relative to the pick roller.

Fig. 5 is an end view of the imaging apparatus shown in Figs. 3 and 4.

Fig. 6 is a side elevation sectional view of the imaging apparatus shown in Figs. 3 through 5, with additional components shown.

Fig. 7 is a side elevation sectional view of the imaging apparatus shown in Fig. 6, with the first and second media trays shown in different positions relative to the pick roller.

Fig. 8 is a side elevation view of an imaging apparatus in accordance with yet another embodiment of the present invention.

Fig. 9 is a side elevation view of the imaging apparatus shown in Fig. 8, with the first and second media trays shown in different positions relative to the pick roller.

DETAILED DESCRIPTION OF THE INVENTION

Apparatus and methods in accordance with the instant invention provide for supporting multiple types of imaging media in respective media trays which, in turn, are supported on an imaging apparatus having only a single pick roller. Any of the imaging media can be selectively presented to the pick roller for picking.

That is, in accordance with one embodiment of the present invention, an imaging apparatus includes a first media tray configured to hold a first imaging media, and a second media tray configured to hold a second imaging media. The imaging apparatus also comprises a pick roller configured to selectively pick the first imaging media from the first media tray and the second media from the second media tray. In other words, the single pick roller is configured to selectively pick media from either the first media tray or the second media tray, one tray at a time. The movement of the first and second

media trays can be facilitated by way of an actuating mechanism that is configured to control the movement of the first and second media trays relative to the pick roller.

In accordance with another embodiment of the present invention, an imaging apparatus includes a first media tray configured to hold a first imaging media, and a second media tray configured to hold a second imaging media. A pick roller is also included in the imaging apparatus, wherein the first media tray is configured to slide relative to the second media tray to facilitate selective presentation of the first imaging media and the second imaging media, one-at-a-time, to the pick roller for picking. An actuating mechanism can also be included, wherein the actuating mechanism is configured to control the movement of the first and second media trays relative to the pick roller.

Another imaging apparatus, in accordance with an embodiment of the present invention, includes a first media tray that has a first lift plate pivotally mounted to it, and wherein a first imaging media is supported on the first lift plate. Likewise, a second media tray is included that has a second lift plate pivotally mounted to it, wherein the second imaging media is supported on the second lift plate. An actuating mechanism can be included as well, wherein the actuating mechanism is configured to cause the first media tray to slide in a direction opposite of that of the second media tray. A lifting device is provided to contact the first and the second lifting plates, one-at-a-time, and to cause to pivot, the respective first and second lift plates. Such pivoting of the first and second lift plates results in presentation of the first and second imaging media, respectively, to a single pick roller on a selective basis.

In accordance with yet another embodiment of the present invention, a method of using a first imaging media and a second imaging media in an imaging device having a single pick roller includes supporting the first and the second imaging media on the imaging device simultaneously. The method also includes picking the first imaging media with the pick roller while the first and second media are simultaneously supported on the imaging device, and also includes picking the second imaging media with the pick roller while the first and second imaging media are simultaneously supported on the imaging device.

Turning now to Fig. 1, a schematic diagram is shown which depicts an imaging apparatus 100 in accordance with one embodiment of the present invention. The imaging apparatus comprises a first media tray 101 that is configured to hold a first imaging media M1. The imaging apparatus 100 also includes a second media tray 102 that is configured to hold a second imaging media M2.

1 A pick roller 120 is also included in the imaging apparatus 100. The pick roller
2 120 is configured to selectively pick the first imaging media M1 from the first media tray
3 101, and is also configured to pick the second media M2 from the second media tray
4 102. That is, the single pick roller 120 is configured to pick both the first imaging media
5 M1 and the second imaging media M2 from the first and second media trays 101 and
6 102, respectively.

7 Turning now to Fig. 2, another schematic diagram is shown which depicts the
8 imaging apparatus 100 shown in Fig. 1. With reference now to both Figs. 1 and 2, the
9 use of the single pick roller 120 to pick the first and second imaging medias M1 and M2
10 is preferably facilitated by way of an actuating mechanism 130 that can be included in
11 the imaging apparatus 100. The actuating mechanism 130 is connected to the first
12 media tray 101, and can also be connected to the second media tray 102.

13 The actuating mechanism 130 is configured to cause the first media tray 101 and
14 the second media tray 102 to be positioned, one-at-a-time, relative to the pick roller 120
15 to thereby present the first imaging media M1 and the second imaging media M2,
16 respectively, to the pick roller for picking. That is, the actuating mechanism is configured
17 to alternately present either the first imaging media M1 or the second imaging media M2
18 to the pick roller 120 for picking.

19 In other words, at any given point in time, either the first media tray 101 or the
20 second media tray 102 is positioned so that either first imaging media M1 or the second
21 imaging media M2, respectively, is presented to the pick roller 120 for picking. For
22 example, it can be assumed that, at a certain point in time, the first media tray 101 is
23 positioned relative to the pick roller 120 so that the first imaging media M1 is presented
24 to the pick roller for picking. The first media tray 101 thus remains at this position while
25 the pick roller 120 picks the required quantity of first imaging media M1 from the first
26 media tray.

27 When the second imaging media M2 is needed at the pick roller 120 for picking,
28 the actuating mechanism 130 is actuated so as to position the second media tray 102
29 relative to the pick roller so that the second imaging media is presented to the pick roller
30 for picking. When the pick roller 120 finishes picking the required quantity of the second
31 imaging media M2, and when the first imaging media M1 is required at the pick roller for
32 picking, the actuating mechanism 130 is actuated so as to position the first media tray
33 101 relative to the pick roller so that the first imaging media is presented to the pick roller
34 for picking.

1 The actuating mechanism 130 can be configured to automatically change the
2 positions of the first and second media trays 101 and 102 by way of an actuator (not
3 shown) or the like, so as to alternately present the first imaging media M1 and the
4 second imaging media M2 to the pick roller for picking. That is, the first imaging media
5 M1 and the second imaging media M2 can be configured to be selectively alternately
6 presented by the actuating mechanism to the pick roller 120 for picking in an automatic
7 fashion by way of an actuator or the like (not show). Examples of how such an actuator
8 can be so employed in conjunction with the present invention will be discussed below
9 with regard to other embodiments of the present invention.

10 The imaging apparatus 100 can also include a controller 198 which is configured
11 to automatically control the actuation of the actuating mechanism 130 in response to
12 predetermined criteria. The predetermined criteria can be, for example, a signal from a
13 host device (not shown) such as a personal computer or the like, to switch from one
14 imaging media to the other. For example, in the case wherein the predetermined criteria
15 is a signal from a personal computer, the signal can originate in a word processing
16 program, wherein a specific type of imaging media is specified thereby.

17 More specifically, for example, a word processing program operating in a
18 personal computer host device can generate a signal which is sent to the controller 198,
19 wherein the signal specifies a change from the first imaging media M1 to the second
20 imaging media M2. Such a situation can arise in a case wherein a document is first
21 printed on standard sheet media, and then an address is to be printed on envelope
22 media.

23 In such a case, and by way of example only, predetermined criteria in the form of
24 a signal originating from the word processing program is received by the controller 198.
25 In response, the controller 198 automatically controls the actuating mechanism 130 so
26 as to present the standard sheet media (e.g. first imaging media M1) to the pick roller
27 120 for picking while the document is printed.

28 This is accomplished by causing the actuating mechanism 130 to position the
29 respective media tray (e.g. first media tray 101) relative to the pick roller 120. When the
30 required quantity of standard sheet media is picked by the pick roller 120, the controller
31 198 controls the actuating mechanism 130 so as to then present the envelope media
32 (e.g. second imaging media M2) to the pick roller 120 for picking while the address is
33 printed on the envelope. When the required quantity of envelope media is picked by the
34 pick roller 120, and when the standard sheet media is again required at the pick roller,

1 the controller 130 again repositions the first and second media trays 101 and 102 so that
2 the standard sheet media is again presented to the pick roller 120 for picking.

3 Such control of the actuating mechanism 130 to alternately position the first and
4 second media trays 101 and 102 relative to the pick roller 120 can alternatively, or
5 additionally, be accomplished manually by way of an input device 199. That is, the
6 imaging apparatus 100 can comprise an input device 199 either in addition to, or as an
7 alternative to, the controller 198. The input device 199 is configured to control the
8 actuation of the actuating mechanism in response to an input from an operator of the
9 imaging apparatus 100. For example, the input device 199 can be in the form of a
10 switch or the like (not shown), which the operator can manipulate so as to position the
11 first and second media trays 101 and 102 relative to the pick roller 120 in order to
12 present the desired first or second imaging media M1 and M2 to the pick roller for
13 picking.

14 In such a case, the operator can print a plurality of documents on the second
15 imaging media M2 by first positioning the second media tray 102 relative to the pick
16 roller 120 so that the second imaging media is presented to the pick roller for picking, as
17 is shown in Fig. 1. The operator can then manipulate the input device 199 so that the
18 actuating mechanism 130 changes the positions of the first and second media trays 101
19 and 102 to thereby present the first imaging media M1 to the pick roller 120 for picking.
20 The operator can then print a plurality of documents on the first imaging media M1.

21 As is seen from a study of Figs. 1 and 2, the imaging apparatus 100 can be
22 configured so that the first media tray 101 and the second media tray 102 remain
23 substantially parallel to one another. However, it is understood that the present
24 invention is not intended to limit the first and second media trays 101 and 102 to being
25 parallel to one another. Also, although the first and second media trays 101 and 102 are
26 shown to be substantially aligned with one another, it is understood that the present
27 invention is not intended to limit the first and second media trays to being aligned with
28 one another, as will become apparent in later discussion.

29 Moving now to Fig. 3, a side elevation sectional view is shown which depicts an
30 imaging apparatus 300 in accordance with another embodiment of the present invention.
31 The imaging apparatus 300 comprises a first media tray 301 that is configured to hold
32 the first imaging media M1. The imaging apparatus 300 also comprises a second media
33 tray 302 that is configured to hold the second imaging media M2. As shown, the first
34 imaging media M1 and the second imaging media M2 can each comprise a plurality of

1 sheets of respective imaging media so as to form respective stacks of imaging media
2 that are supported on the respective first and second media trays 301 and 302.

3 The imaging apparatus 300 also comprises a pick roller 120 which is described
4 above with respect to the imaging apparatus 100 which is shown in Figs. 1 and 2. As is
5 further shown, the imaging apparatus 300 preferably comprises a chassis 340 on which
6 the remainder of the apparatus can be supported. A frame 341 is also preferably
7 included in the apparatus 300, and is more preferably supported on the chassis. The
8 frame 341 and the chassis 340 are preferably configured to remain stationary relative to
9 the pick roller 120. Furthermore, the frame 341 and the chassis 340 together can act to
10 stabilize the first and the second media trays 301 and 302 as the trays move relative to
11 the pick roller 120. That is, the frame 341 preferably acts to maintain the functional
12 alignment of the first and second media trays 301 and 302.

13 As further shown in Fig. 3, the first media tray 301 and the second media tray 302
14 are each preferably configured to function similarly to the first and second media trays
15 101 and 102 of the apparatus 100 which is described above and shown in Figs. 1 and 2.
16 That is, the pick roller 120 is configured to selectively pick the first imaging media M1
17 from the first media tray 301, and is further configured to pick the second imaging media
18 M2 from the second media tray 302, wherein respective imaging media is picked from
19 one tray at a time.

20 Preferably, the first media tray 301 of the imaging apparatus 300 is slidably
21 disposed upon the second media tray 302 of the apparatus. Accordingly, the first media
22 tray 301 is configured to slide relative to the second media tray in order to facilitate
23 selective presentation of the first imaging media M1 and the second imaging media M2,
24 one-at-a-time, to the pick roller for picking. That is, in the manner described above with
25 respect to the imaging apparatus 100, the imaging apparatus 300 is configured so that
26 the first media tray 301 and the second media tray 302 can be positioned, one-at-a-time
27 relative to the pick roller 120 to thereby present the first media M1 and the second media
28 M2, respectively, to the pick roller for picking.

29 In order to facilitate the alternate presentation of the first imaging media M1 and
30 the second imaging media M2 to the pick roller 120, the imaging apparatus 300
31 preferably comprises an actuating mechanism 350. The actuating mechanism 350
32 comprises a gear rack 351 that is supported on the first media tray 301. The actuating
33 mechanism 350 also comprises a pinion gear 353 that is meshingly engaged with the
34 gear rack 351. As is seen from a study of Fig. 3, the rotation of the pinion gear 353
35 causes the first media tray 301 to slide relative to the second media tray 302.

1 Turning now to Fig. 4, another side elevation sectional view is shown which
2 depicts the imaging apparatus 300 that is shown in Fig. 3. It is evident that Figs. 3 and 4
3 are identical, with the exception that the first and second media trays 301 and 302 are
4 shown in opposite positions relative to the pick roller 120. As is also seen, the actuating
5 mechanism 350 preferably comprises a pair of gear racks 351, wherein one of the gear
6 racks is supported on the first media tray 301, and the other of the gear racks is
7 supported on the second media tray 302. Accordingly, the pinion gear 353 is preferably
8 meshingly engaged with each of the gear racks 351.

9 It is understood from a study of Figs. 3 and 4, that an operator can manipulate
10 the first and second media trays 301 and 302 so as to selectively and alternatively
11 position each media tray relative to the pick roller 120 so that either the first media M1 or
12 the second media M2 is presented to the pick roller for picking. That is, in accordance
13 with the present invention, the first and/or second media trays 301 and 302 can be
14 moved manually by an operator so as to selectively position either the first media tray
15 301 or the second media tray 302 at the pick roller 120 so as to present either the first
16 media M1 or the second media M2 to the pick roller for picking.

17 Turning now to Fig. 5, an end view is shown of the apparatus 300 which is shown
18 in Figs. 3 and 4. As is seen in Fig. 5, the imaging apparatus 300 preferably comprises
19 an actuator 360 that is configured to cause the pinion gear 353 to rotate. The actuator
20 360 can be, for example, a rotary actuator such as a stepper motor or the like. As is
21 also seen, the frame 341 and the chassis 340 preferably surround both the first and
22 second media trays 301 and 302 so as to stabilize the trays during movement thereof. It
23 is understood that, for reasons of clarity, Figs. 3 through 5 show only a portion of the
24 components that are contemplated for inclusion into the imaging apparatus 300, and that
25 other components will be described below with reference to additional figures.

26 Returning now to Figs. 3 and 4, it is seen that, rotation of the pinion gear 353 in a
27 first direction causes the first media tray 301 to move toward the pick roller 120, while
28 rotation of the pinion gear in a second direction opposite the first direction causes the
29 first media tray to move away from the pick roller. Likewise, rotation of the pinion gear
30 353 in the first direction can cause the second media tray 302 to move away from the
31 pick roller 120, while rotation of the pinion gear in the second direction can cause the
32 second media tray to move toward the pick roller.

33 Turning now to Figs. 6 and 7, respective side elevation sectional views are shown
34 of the imaging apparatus 300 that is depicted in Figs. 3 through 5. As is evident from an
35 examination of Figs. 6 and 7, additional components of the apparatus 300 are shown

1 which are omitted from Figs. 3 through 5 for reasons of clarity, as explained above. It is
2 also understood that other components of the imaging apparatus 300 which are
3 described above and shown in Figs. 3 through 5 have been omitted from Figs. 6 and 7
4 for reasons of clarity.

5 With reference to Figs. 6 and 7, the imaging apparatus 300 can additionally
6 comprise a first lift plate 371 that is configured to support thereon the first imaging media
7 M1. The first lift plate 371 is pivotally connected to the first media tray 301 so as to be
8 pivotable relative thereto as shown. Likewise, the imaging apparatus 300 can also
9 comprise a second lift plate 372 that is configured to support thereon the second
10 imaging media M2. Similarly, the second lift plate 372 is pivotally connected to the
11 second media tray 302 so as to be pivotable relative thereto as is also shown.

12 The apparatus 300 preferably comprises a lifting device 380 positioned as shown
13 relative to the pick roller 120 and to the first and second media trays 301 and 302. The
14 lifting device 380 is configured to cause the first lift plate 371 and the second lift plate
15 372 to pivot, one-at-a-time, relative to the first media tray 301 and to the second media
16 tray 302, respectively, in order to facilitate presentation of the first imaging media M1
17 and the second imaging media M2, respectively, to the pick roller 120 for picking. The
18 lifting device 380 preferably comprises a lifting member 381 that is configured to pivot
19 relative to the first and second media trays 301 and 302. The lifting device 380 also
20 preferably comprises a biasing member 382 configured to contact the lifting member 381
21 and to thereby urge the lifting member toward the first lift plate 371 and toward the
22 second lift plate 372 to facilitate pivoting thereof by the lifting member.

23 It is understood that the lifting device 380 can be a passive lifting device or an
24 active lifting device. That is, the lifting device 380 can be configured to perform
25 passively, wherein the biasing member 382 is a resilient member such as a spring or the
26 like. In such a passively operational configuration, the lifting device 380 depends upon
27 the movement of the first and second media trays 301 and 302 there against in order to
28 perform its function. Alternatively, the lifting device 380 can be configured to perform
29 actively, wherein the biasing member 382 is an actively controlled actuator or the like. In
30 such an actively operational configuration, the lifting device functions actively in
31 response to a signal from a controller or the like, such as the controller 198 shown in
32 Figs. 1 and 2.

33 Thus, as shown in Fig. 6, wherein the lifting device 380 is configured to operate
34 passively, it is seen that the movement of the first media tray 301 toward the pick roller
35 120 causes the first lift plate 371 to contact the lifting member 381, and to thereby pivot

1 so as to present the first media M1 to the pick roller 120. Likewise, as shown in Fig. 7,
2 movement of the second media tray 302 toward the pick roller 120 causes the second lift
3 plate 372 to contact the lifting member 381, and to thereby pivot so as to present the
4 second media M2 to the pick roller 120.

5 It is also seen, with reference to Figs. 3 and 4 as well as Figs. 6 and 7, that
6 rotation of the pinion gear 353 in a first direction causes the first imaging media M1 to be
7 presented to the pick roller 120, while rotation of the pinion gear in a second direction
8 opposite the first direction causes the second imaging media M2 to be presented to the
9 pick roller 120. As explained above, such rotation of the pinion gear 353 can be caused
10 by manual movement by an operator of the first and/or second media trays 301 and 302,
11 or by automatic rotation of the pinion gear by way of the actuator 360.

12 Now moving to Figs. 8 and 9, respective side elevation views are shown in which
13 an imaging apparatus 800 is depicted in accordance with yet another embodiment of the
14 present invention. The imaging apparatus 800 comprises a first media tray 801
15 configured to hold the first imaging media M1. A second media tray 802 is also included
16 in the imaging apparatus 800, wherein the second media tray is configured to hold a
17 second imaging media M2. The imaging apparatus also comprises a pick roller 120 that
18 is configured to selectively pick the first imaging media M1 from the first media tray 801,
19 and the second imaging media M2 from the second media tray 802, wherein the
20 respective media is picked from one tray at a time.

21 The imaging apparatus 800 also preferably comprises an actuating mechanism
22 880 that is connected to the first media tray 801. The actuating mechanism 880 is
23 preferably configured to cause the first media tray 801 and the second media tray 802 to
24 be positioned, one-at-a-time, relative to the pick roller 120 to thereby present the first
25 imaging media M1 and the second imaging media M2 to the pick roller for picking. That
26 is, the imaging apparatus 800 is configured to selectively alternately present the first
27 imaging media M1 and the second imaging media M2 to the pick roller.

28 Preferably, the apparatus 800 also comprises a chassis 810 that is configured to
29 serve as a structural support for one or more components of the apparatus. The pick
30 roller 120 is preferably operationally supported on the chassis 810 as shown. The
31 second media tray 802 is also preferably movably supported on the chassis 810, while
32 the first media tray 801 is slidably supported on the second media tray. That is, the first
33 media tray 801 is preferably supported on the second media tray 802 so as to slide
34 relative thereto as suggested by an examination of both Figs. 8 and 9.

1 More specifically, sliding the first media tray 801 in a first direction relative to the
2 second media tray 802 results in presentation of the first imaging media to the pick roller
3 for picking. Likewise, sliding the first media tray 801 in a second direction, which is
4 opposite of the first direction, results in presentation of the second imaging media M2 to
5 the pick roller 120 for picking.

6 A pivot axis 860 can be defined on the second media tray 802, as shown. The
7 second media tray 802 can thus be pivotally connected to the chassis 810 and thereby
8 configured to pivot about the pivot axis 860. As is seen from a study of both Figs. 8 and
9 9, movement of the first media tray 801 relative to the second media tray 802 causes the
10 second media tray to pivot about the pivot axis 860. This pivoting of the second media
11 tray 802 as the result of movement relative thereto of the first media tray 801 can be
12 achieved by way of the operation of the actuating mechanism 880.

13 Preferably, the actuating mechanism 880 is in the form of an elongated member,
14 as shown. The actuating mechanism 880, in the form of an elongated member, has a
15 first end 881 that is pivotally connected to the first media tray 801, and a distal opposite
16 second end 882 that is pivotally connected to the chassis 810. Thus, as is seen from an
17 examination of both Figs. 8 and 9, the actuating mechanism 880 causes the first media
18 tray 801, when sliding relative to the second media tray 802, to move in a substantially
19 arcuate manner about the second end 882 and relative to the chassis 810.

20 It is understood that the actuating mechanism 880 can be configured in any of
21 several possible manners. For example, as an alternative to the configuration of the
22 actuating mechanism 880 which is described above and shown in Figs. 8 and 9, the
23 actuating mechanism can comprise a cam surface (not shown) and a cam follower (not
24 shown). More specifically, in such an alternative configuration, the cam surface can be
25 supported or defined on the chassis 810. Likewise, the cam follower can be mounted on
26 the first media tray 801 and configured to follow the cam surface as the result of
27 movement of the first media tray relative to the second media tray 802.

28 As a view of Figs. 8 and 9 reveals, the second media tray 802 can have a first
29 end 811 and an opposite distal second end 812. The second imaging media M2 is
30 preferably positioned proximate the second end 812 as shown, while the pivot axis 860
31 is preferably defined proximate the first end 811. As is also revealed from a study of
32 Figs. 8 and 9, movement of the first media tray 801 toward the second end of the second
33 media tray 802 results in the presentation of the first media M1 to the pick roller 120,
34 while movement of the first media tray toward the first end 811 of the second media tray
35 results in presentation of the second media M2 to the pick roller. As is further seen, the

1 first media tray 801 and the second media tray 802 preferably remain substantially
2 parallel to one another.

3 The imaging apparatus 800 preferably comprises a biasing member 882 which is
4 connected between the chassis 810 and the second media tray 802. The biasing
5 member 882 is preferably configured to bias the second media tray 802 toward the pick
6 roller 120. The imaging apparatus 800 also preferably comprises an actuator 850. The
7 actuator 850 is preferably connected to the first media tray 801 and is configured to
8 selectively cause the first media tray to slide relative to the second media tray 802 to
9 facilitate presentation of the first media M1 and the second media M2, one-at-a-time, to
10 the pick roller 120 for picking. It is understood that the actuator 850 can have one of
11 many possible alternative positions and configurations other than that specifically shown.

12 As shown, the actuator 850 can be in the form of a linear actuator as shown,
13 which can include, for example, a hydraulic or pneumatic cylinder assembly, a linear
14 motor, or the like. The actuator 850, when configured as a linear actuator, can be
15 connected between the first media tray 801 and the second media tray 802 as shown.
16 Alternatively, the actuator 850, when configured as a linear actuator, can be connected,
17 by way of pivot connections (not shown), between the first media tray 801 and the
18 chassis 810.

19 As yet a further alternative, the actuator 850 and the actuating mechanism 880
20 can be integrated with one another. For example, the actuating mechanism 880 can be
21 alternatively replaced by a rotary actuator (not shown) connected between the chassis
22 810 and the first media tray 801, and which is configured to serve as both the actuating
23 device as well as the actuator to move the first media tray relative to the second media
24 tray 802.

25 In accordance with yet another embodiment of the present invention, a method of
26 using a first imaging media and a second imaging media in an imaging apparatus having
27 a pick roller is disclosed. The method includes supporting the first imaging media and
28 the second imaging media on the imaging apparatus simultaneously. While the first
29 imaging media and the second imaging media are supported simultaneously on the
30 imaging apparatus, the first imaging media is picked by the pick roller. Likewise, the
31 second imaging media is also picked by the pick roller while the first imaging media and
32 the second imaging media are supported simultaneously on the imaging apparatus.

33 That is, while the first imaging media and the second imaging media are
34 supported on the imaging apparatus, the first imaging media is presented to the pick
35 roller for picking by moving the first imaging media into contact with the pick roller.

1 When the second imaging media is to be picked, the first imaging media is moved out of
2 contact with the pick roller, and the second imaging media is presented to the pick roller
3 by moving the second imaging media into contact with the pick roller.

4 While the above invention has been described in language more or less specific
5 as to structural and methodical features, it is to be understood, however, that the
6 invention is not limited to the specific features shown and described, since the means
7 herein disclosed comprise preferred forms of putting the invention into effect. The
8 invention is, therefore, claimed in any of its forms or modifications within the proper
9 scope of the appended claims appropriately interpreted in accordance with the doctrine
10 of equivalents.

11